

**LOFTSTIGER – GYLDIGHEDSOMRÅDE FOR CERTIFIKAT**

Certifikatindehaver: Dolle A/S  
Vestergade 47  
7741 Frøstrup

Certifikatnummer: 8053 og 8053-01

Certifikat udstedt: 2023-06-15  
Gyldighedsområde opdateret: 2023-06-15

**Følgende produkter er omfattet af ovennævnte certifikat med deklareret ydeevne i henhold til DS/EN 14975:2006+A1:2010:**

	ClickFix 76 - Product name				REI 60**		REI 45**	
	ClickFix 76 Gold		ClickFix 76 Comfort	ClickFix 76 Vario	Wooden ladder	Aluminium concertina ladder	Wooden ladder	Steel ladder
Insulation material* : EPS	ClickFix 76 Thermo		ClickFix 76 Thermo Comfort	ClickFix 76 Thermo Vario				
Insulation material* : PUR	ClickFix 76 Thermo		ClickFix 76 Thermo Comfort	ClickFix 76 Thermo Vario				
Ladder material	Wooden ladder		Steel ladder	Aluminium concertina ladder	Wooden ladder	Aluminium concertina ladder	Wooden ladder	Steel ladder
Type of ladder	Hinged/folding loft ladder	Hinged/folding loft ladder	Hinged/folding loft ladder	Concertina loft ladder	Hinged/folding loft ladder	Concertina loft ladder	Hinged/folding loft ladder	Hinged/folding loft ladder
Size	12 treads	14 treads	12 treads	9-14 treads	12 treads	9-14 treads	12 treads	12 treads
Hatch dimensions up to	1375 x 676 mm	1375 x 676 mm	1375 x 676 mm	1375 x 676 mm	1175 x 676 mm	1175 x 676 mm	1375 x 676 mm	1375 x 676 mm
Max load	150 kg	150 kg	150 kg	150 kg	150 kg	150 kg	150 kg	150 kg
Applicable handrail	Steel handrail for wooden ladders (K1-21220)	Steel handrail for wooden ladders (K1-21220)	Telescopic steel handrail (K2-16330)	9-11 treads: Telescopic aluminium handrail no. 1006002  12-14 treads: Telescopic aluminium handrail no. 1006003	Steel handrail for wooden ladders (K1-21220)	9-11 treads: Telescopic aluminium handrail (1006002)  12-14 treads: Telescopic aluminium handrail (1006003)	Steel handrail for wooden ladders (K1-21220)	Telescopic steel handrail (K2-16330)
5.6 - Ladder stops test	NA	NA	NA	NA	NA	NA	NA	NA
Deviations from EN 14975	-	-	-	Clause 6.6: $l_1$ exceeds requirement of max 300 mm	-	Clause 6.6: $l_1$ exceeds requirement of max 300 mm	-	-

\*Thermal insulation performance is not covered by this certificate.

\*\*Resistance to fire performance is not covered by this certificate.

Auditor Stine Lønbro Bertelsen